

Declaration of performance No. 4/22

1. Unique identification code of the product type:

Dry-pressed ceramic tiles with water absorption $E_b \leq 0,5\%$

2. Intended use or uses:

The material is intended for laying floors and walls internal and/or external.

3. Manufacturer:

Ceramika Tubądzin Sp. z o.o.

Tubądzin 31

98-285 Wróblew

www.tubadzin.pl

4. System of assessment and verification of constancy of performance of the construction:

System : 4

5. Harmonized standard:

EN 14411:2012

6. Declared performance:

Essential characteristics	Performance (level and/or class)	Harmonized technical specification
Reaction to fire	A1 / A1 _{FL}	BS EN 14411:2012
Breaking strength:		
Thickness $\geq 7,5$ mm	≥ 1300 N	
Thickness $< 7,5$ mm	≥ 700 N	
Release of dangerous substances		
- Cadmium	$< 0,01$ mg/dm ²	
- Lead	$< 0,01$ mg/dm ²	
Bond strength / adhesion		
Cementitious adhesion	$\geq 1,0$ Mpa	
Dispersion adhesives	NPD	
Reaction resin adhesives	$\geq 2,0$ Mpa	
Mortar	NPD	
Slipperiness according to CEN/TS 16165:2012, Annex B	$\leq R13$	
Resistance to thermal shock	Meets	
Durability for:		
- internal uses	Meets	
- external uses: freeze-thaw resistance	Meets	
Tactility	NPD – no performance determined	

7. Relevant technical documentation or special technical documentation:

ND – not applicable

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signature on behalf of the manufacturer:

DYREKTOR GENERALNY


Paweł Gwiazda

Tubądzin 25.11.2022

GŁÓWNY TECHNOLOG


Kamil Królak

PREZES ZARZĄDU


Mirosław Jędrzejczyk