

1. **The unique identification code of the product type:** Dry-pressed ceramic tiles with water absorption $E_b \leq 0,5\%$
2. **Intended use or uses:** Material intended for finishing internal and/or external floor and wall coverings.
3. **Manufacturer:** Ceramika Tubądzin III Sp z o.o. Sp. k., ul. Dworska 28, 98-200 Sieradz, Polska, website: www.tubadzyn.pl
4. **Authorised representative:** ND - not applicable
5. **System(s) of assessment and verification of constancy of performance:** Assessment system: 4
- 6a. **Harmonised standard:** EN14411:2012
Notified body/ies: NA - not applicable No. NA - not applicable
- 6b. **European Assessment Document:** NA - not applicable
European Technical Assessment: NA - not applicable
Technical Assessment Body: NA - not applicable
7. **Declared performances:**

ESSENTIAL CHARACTERISTICS OF THE PRODUCT	DECLARED PERFORMANCES
Reaction to fire:	A1 / A1_{FL}
Breaking strength for:	
thickness $\geq 7,5$ mm	≥ 1300 N
thickness $< 7,5$ mm	≥ 700 N
Release of dangerous substances, for:	
-Cadmium	$< 0,01$ mg/dm ²
-Lead	$< 0,01$ mg/dm ²
Bond strength / adhesion, for:	
Cementitious adhesives	$\geq 1,0$ Mpa
Dispersion adhesives	NPD
Reaction resin adhesives	$\geq 2,0$ Mpa
Masonry mortar	NPD
Slipp resistance according to CEN / TS 16165: 2012, Annex B	$\leq R13$
Thermal shock resistance	Pass
Durability, for:	
- internal applications	Pass
- external applications: freeze-thaw resistance	Pass
Tactility	NPD

NPD - No Performance Declared

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the above specified product is compliant with the set of declared performance. This declaration of performance has been issued in line with the regulation (UE) no. 305/2011 under the sole responsibility of the above specified manufacturer.

Signed for and on behalf of the manufacturer by:

Monika Paplernik Chief Technologist



Sieradz, on 04.04.2022.

Updated on the basis of the Declaration of Performance of 06.07.2021