

UK DECLARATION OF CONFORMITY No 1/22

1. **The unique identification code of the product type:** Dry-pressed ceramic tiles with water absorption $E_v \leq 0,5\%$
2. **Intended use or uses:** Material intended for finishing internal and/or external floor and wall coverings.
3. **Manufacturer:** Ceramika Tubądzin III Limited Liability Company, Limited Partnership., ul. Dworska 28, 98-200 Sieradz, Polska, website: www.tubadzin.pl
4. **Authorised representative:** NA - not applicable
5. **System(s) of assessment and verification of constancy of performance:** Assessment system: 4
- 6a. **Notified body/ies:** NA - not applicable
- 6b. **Harmonised standard:** EN14411:2012
7. **Declared performances:**

ESSENTIAL CHARACTERISTICS OF THE PRODUCT	DECLARED PERFORMANCES
Reaction to fire:	A1 / A1 _{FL}
Breaking strenght for:	
thickness $\geq 7,5$ mm	≥ 1300 N
thickness $< 7,5$ mm	≥ 700 N
Release of dangerous substances, for:	
-Cadmium	$< 0,01$ mg/dm ²
-Lead	$< 0,01$ mg/dm ²
Bond strenght / adhesion, for:	
Cementitious adhesives	$\geq 1,0$ MPa
Dispersion adhesives	NPD
Reaction resin adhesives	$\geq 2,0$ MPa
Masonry mortar	NPD
Slipp resistance according to CEN / TS 16165: 2012, Annex B	$\leq R13$
Thermal shock resistance	Compliant
Durability, for:	
- internal applications	Compliant
- external applications: freeze-thaw resistance	Compliant
Tactility	NPD

NPD - No Performance Declared

8. **Appropriate Technical Documentation and/or Specific Technical Documentation:** NA - not applicable

The performance of the above specified product is compliant with the set of declared performance. This declaration of performance has been issued under the sole responsibility of the above specified manufacturer.

Signed for and on behalf of the manufacturer by:
President of the Board of the General Partner
Mirosław Jędrzejczyk



Member of the Board of the General Partner
Paweł Oskard



Sieradz, on 30.12.2022

