

1. The unique identification code of the product type:

Dry pressed ceramic tiles with water absorption $E_b \leq 0,5\%$

2. Usage and intended application:

Material intended for finishing internal and/or external floor and wall coverings

3. Manufacturer:

Ceramika Tubądzin II Sp. z o.o.

ul. Armii Krajowej 20, 95-035 Ozorków,

Polska

www.tubadzin.pl

4. Authorised representative: ND –not applicable**5. System of assessment and verification of constancy of performance of the construction:**

Assessment system 4

6. Harmonized standard: EN 14411:2012**7. Declared performance**

Essential characteristics	Performance	Technical specification
Reaction to fire	A1 / A1 _{FL}	EN 14411:2012
Breaking strength [N]	≥ 1300	
Release of dangerous substances, for: -cadmium [mg/dm ²] -lead [mg/dm ²]	< 0,01 < 0,01	
Binding strength / adhesion [N/mm ²]: - Cement adhesives - Dispersion adhesives - Reactive resin adhesives - masonry mortar	$\geq 1,0$ NPD* $\geq 2,0$ NPD*	
Slip resistance according to CEN/TS 16165:2012, Annex B	$\leq R13$	
Durability for: - Interior applications - Exterior applications: freeze – thaw resistance (frost resistance)	Compliant Compliant	
Resistance to thermal shock	Compliant	
Touch sensation	NPD*	

* no performance defined

8. Appropriate technical documentation or special technical documentation:

The performance of the above specified product is compliant with the set of declared performance. This declaration of performance has been issued under the sole responsibility of the above specified manufacturer.

Signature on behalf of the manufacturer by:

Mirosław Jędrzejczyk

President of the Board

Ozorków, 22-12-2022

Karol Chmielewski

Vice President of the Board