

1. **Unique identification code of the product:** Dry-pressed ceramic tiles with water absorptivity E>10%
2. **Intended use (s):** The material is intended for laying of the internal walls.
3. **Manufacturer:**
 Ceramika Tubądzin II spółka z ograniczoną odpowiedzialnością (Limited Liability Company)
 Armii Krajowej 20, 95-035 Ozorków, Poland
 Website: www.tubadzin.pl
4. **Authorised representative:** ND - not applicable
5. **System(s) of assessment and verification of stability of performance:** Assessment system: 4
- 6a. **Harmonised standard:** EN14411:2012
Notified body/ies: NA - not applicable No. NA - not applicable
- 6b. **European Assessment Document:** NA - not applicable
European Technical Assessment: NA - not applicable
Technical Assessment Body: NA - not applicable
7. **Declared performances:**

| ESSENTIAL CHARACTERISTICS OF THE PRODUCT | DECLARED PERFORMANCES | Technical Specification |
|---|------------------------------|-------------------------|
| Reaction to fire: | A1 | EN 14411:2012 |
| Release of dangerous substances, for: - Cadmium [mg/dm ²] - Lead [mg/dm ²] | < 0,01 < 0,01 | |
| Binding force/adhesion, for: [N/mm²] - Cement adhesives - Dispersion adhesives - Reaction resin adhesive - Masonry mortar | ≥1,0 ≥1,0 ≥2,0 NPD* | |
| Thermal shock resistance | Compliant | |
| Durability, for: - interior applications - external applications: freeze-thaw resistance | Compliant NPD* | |

* NPD - No Performance Declared

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance for the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mirosław Jędrzejczyk
 President of the Board

Karol Chmielewski
 Vice-President of the Board